

Technical manual №6.03. Version dated 10.2014.

## Bitumen emulsion Primer TECHNOMICOL № 04

TU 5775-006-72746455-2007

### Product description

Bitumen emulsion Primer TECHNOMICOL № 04 is a ready-to-use material, which is an water emulsion of oil bitumen modified with processing additives. Does not contain solvents.

### Area of application

It is used for:

- Indoors and outdoors surface preparation;
- preparing (priming) of waterproofing surfaces (concrete slab, cement-sand screed, etc.) before waterproofing with fusing and self-adhesive materials.

Primer consumption —0.25 –0.35 l/m<sup>2</sup>.



### Main characteristics

Indicator name	Unit	Value	Testing method
Content of bitumen with emulsifier, in the range of	%	25-40	GOST R 52128
Softening point, at least	°C	75	-  -
Relative viscosity at (20.0±0.5) °C, in the range of	s	5-30	-  -
Drying time, at most	h	1	TU 5775-007-72746455-2007

### Performance of works

According to the General Guidelines for design and construction of roofs of bitumen-polymer fusing materials TechnoNICOL Corporation, the Guidelines for the waterproofing of underground structures TechnoNICOL Corporation.

Temperature range from +5°C to +30°C.

Drying time under standard conditions is not more than 1 hour.

The product is water based, does not contain organic solvents. Avoid contact with skin and eyes.

### Storage

Keep in a dry place, away from the sun light at temperature at least +5°C.

Guaranteed shelf life - 6 months.

### Packaging Information

Metal eurobuckets 10 and 20 l.